



**RX**



**DECK**

- Mechanically driven 3 point hitch mounted rotary mower
- 17.5" offset adapter for the RX 96 models for use with select side mowers
- Features a stump jumper blade pan assembly



**GEARBOX**

- Features a 130 HP rated mechanical gear box with a 5 year manufacturer's warranty
- CAT IV Drivelines with plastic safety shielding for safety and durability



**CHAINGUARDS**

- Sturdy 10 gauge deck construction with front and rear double chain guards for safety



**REAR TAILWHEEL**

- Features laminated rear tires with 36 degree swivel fork

RX SERIES SPECIFICATIONS	60" MODEL	72" MODEL	84" MODEL	96" MODEL
Cutting Width	60"	72"	84"	96"
Overall Width	67.5"	79.5"	89.5"	101.5"
Overall Length	111"	123"	138.5"	150.5"
Equipment Weight	998 lbs	1,158 lbs	1,540 lbs	2,004 lbs
Cutting Heights	1.5" to 12"	1.5" to 12"	1.5" to 12"	1.5" to 12"
Cutting Capacity	2.5" grass & brush	2.5" grass & brush	2.5" grass & brush	2.5" grass & brush



TRACTOR REQUIREMENTS	60" MODEL	72" MODEL	84" MODEL	96" MODEL
Minimum Weight	2,500 lbs	3,500 lbs	3,500 lbs	3,500 lbs
3-Point Lifting Capacity	1,000 lbs	1,200 lbs	2,000 lbs	2,000 lbs
Minimum PTO	35 HP	45 HP	60 HP	70 HP
Hitch	CAT I rear 3-point hitch, CAT II hitch adapters are available	CAT I rear 3-point hitch, CAT II hitch adapters are available	CAT II rear 3-point hitch, CAT III hitch adapters are available	CAT II rear 3-point hitch, CAT III hitch adapters are available
PTO Shaft	540 RPM, 1 3/8" 6-spline	540 RPM, 1 3/8" 6-spline	540 RPM, 1 3/8" 6-spline	540 RPM, 1 3/8" 6-spline
ROPS	Certified Roll-Over Protective Structure (ROPS) or ROPS cab and seat belt	Certified Roll-Over Protective Structure (ROPS) or ROPS cab and seat belt	Certified Roll-Over Protective Structure (ROPS) or ROPS cab and seat belt	Certified Roll-Over Protective Structure (ROPS) or ROPS cab and seat belt



**RX™**

**ALAMO INDUSTRIAL**

**BUILT SHARPER**

A Member of Alamo Group