












The Wave® and Vertex® are dual threats with their patented dual-wall polished extrusions made of strong, long-lasting aluminum. Their walls are surprisingly thin without compromising on toughness. The polished outer walls give the bodies a distinctive look, while sturdy inner walls and stiffeners hide dents and dings. The Wave® and Vertex® feature aerodynamic, fuel-saving sides; rubber seal tailgates; and patented SST-shaped crossmembers for optimal performance in the field.







THE WAVE® SPECIFICATIONS	
Body Width	96"
Body Lengths	14' - 26' (1' increments only)
Side Heights	48", 54", 60" or 66"
Floor Sheet	.250 5454 H34 Aluminum Alloy
Side Wall	Horizontal Dual Wall 6005A-T61 Alum. Extrusion 2 5/8 " Hollow Core with Inner Stiffeners
Top Rail	6 x 2 5/8" Top Rail, 1/2" Thick Upper Cross Section
Rub Rail	6 x 2 3/4" Extruded 6005A-T61
Nose Panel	.250" 5454 H32
Tailgate	Sealed, Air Operated Latch
Floor Supports	5.5" SST Crossmembers
Rear Apron	Alum. Length Optional
Weight	2500 lbs. (14' x 48")

AVAILABLE OPTIONS:

- 8", 10", 12" Apron (Bolt-on -or- weld-on)
- 16" Apron (Bolt-on Only)
- 6"-12" Board Pockets
- Side wall insulation

- Two-Way/Barn Door Tailgate
- Coal/Grain Door Tailgate
- Rigid or Folding Ladder
- Narrow (24"x65") or Full-Width (24"x96") Cabshield



1425 Highway 25 North Tishomingo, MS 38873 800.255.4345 Fax: 800.728.4345 www.**duraclass**.com SOLD BY: