

Multi-functional flail mower



Professionals who choose Votex, choose powerful machines that deliver maximum performance in all conditions. Whether your business is managing verges, ditches, gardens and parks, or your business is in agriculture or horticulture, Votex machines have been developed to enable you to work safe and responsible. You can also be sure of the best result and an attractive rate per square metre. Votex machines are used in more than 25 countries.

- Verges and ditches
- Garden, park and public greenery
- Agriculture and horticulture
- Mowers
- Blowers
- Vacuum units and trailers



Alamo Industrial*

Sales@Alamo-Industrial.com

1502 E Walnut St, Seguin, TX 78155 | 800-882-5762 | www.alamo-industrial.com

The incredibly versatile flail mower

The RoadFlex unites the side flail mower and the in-line flail mower into a single machine. A side shift of almost 250 cm enables the machine to mow at the rear as well as the side of the tractor. The mowing head is always close to the rear of the tractor so that the centre of gravity lies close to the rear axle. A unique feature of the RoadFlex is the three-point linkage with its hydraulic break away system. This system provides protection against collisions with obstacles and increases comfort during mowing activities. In addition, it reduces the strain on the flail mower chassis and the lifting device of the tractor. This benefits the mower's lifecycle.

- Side shift of almost 250 cm
- Can work behind or beside the tractor
- Hydraulic break away system
- Quick manoeuvring around obstacles
- Extremely short to the tractor for optimum control
- Very high comfort for the driver
- Works more efficient and quick
- Optional: a rotor axle with 1,3 kg hammerflails



Specifications RoadFlex			
Frame	150	190	210
Mouting position	Rear		
Category	Category II		
Safety break system	Hydraulically to the front and rear		
Side shift	Hydraulically with arm and parallel guidance		
Maximal displacement	244 cm		
Mowing angle	-60° up to +90°		
Maximum reach (relative to tractor axis)	320 cm	356 cm	374 cm
Mowing head	Ecomow®		
Flails	325 grammes per piece		
Weight 40 x 12 flail	325 grammes per piece		
Number of 40 x 12 flails	48	60	66
Weight hammer flail	1300 grammes per piece		
Number of hammer flails	16	20	22
Power train	Silent box with helical tooth profile		
PTO power (min)	40 kW (54 HP)	50 kW (68 HP)	60 kW (82 HP)
PTO speed	540 rpm		
Gearbox	Silent box with helical tooth profile		
Dimensions	Silent box with helical tooth profile		
Cutting width	147 cm	181 cm	199 cm
Overall width	208 cm	244 cm	262 cm
Weight (from)	1200 kg	1235 kg	1250 kg



Alamo Industrial®

Sales@Alamo-Industrial.com

1502 E Walnut St, Seguin, TX 78155 | 800-882-5762 | www.alamo-industrial.com